


- Bespoke linear lengths and shaped designs. Corner sections, connection joints are fully illuminated no dark or bright spot
- LED Fusion recessed light suspended or surface linear light-line microprism diffuser for glare free illumination to EN12464-1 UGR<19, Opal diffuser for uniform light transmission
- Available as single unit or Continuous Seamless line of light in any length
- Suspended version supplied with 3 meter height adjustable wire suspension, integral driver
- Aluminium-profile anodised matt silver body. Available on request to any powder coated RAL finish
- IP42
- Suspended or surface mounted LED luminaire, rectangular shape

Options

- DALI / DSI digital dimmable control gear integral
- 3 hour emergency
- Standard LED colour temperature 4000K CRI>80 or CRI>90
- Option 2700, 3000, 5000K and tunable



Add suffix to catalogue number:

EM3: 3 hour emergency. **EM3ST:** 3 hour self test emergency.

EM3DALI: DALI Addressable emergency. **SD:** Dimming with push to make switch. **DALI:** Digital Addressable Lighting Interface.

Please note that with the continuous rapid development in lighting technology, specification values may change. Contact our technical department for details. We reserve the right to amend or change details without prior notification. All performance data is taken at an ambient temperature of +25°C. Lumens and connected system load are subject to an initial tolerance of up to +/- 10%.

FUSION50 SPECIFICATION

CAT No	Colour Temp (K)	Colour Rendering (RA)	Life (L80) (hrs)	Total Connected Load	Total Delivered Lumens	Circuit Efficacy (lm/W)	L (mm)
FUSM08	4000	80	60000	7.5	825	110	570
FUSM12	4000	80	60000	12	1330	110	570
FUSM15	4000	80	60000	15	1650	110	1130
FUSM25	4000	80	60000	25	2780	110	1130
FUSM30	4000	80	60000	30	3370	112	1410
FUSM37	4000	80	60000	37	4144	112	1410
FUSM45	4000	80	60000	45	5040	112	1680
FUSM54	4000	80	60000	54	6048	112	1960
FUSM48	4000	80	60000	50	5560	112	2240

Above are standard lumens, lower and higher lumens available

