



- Flat LED luminaire
- Efficient LED edge lit micro prism optic
- Powder coated matt white extruded aluminium frame
- Glare control UGR <19
- Office lighting complying with EN 12464
- Suitable for lay-in installation into 15mm or 24mm
- Diffuser material standard : PS, diffuser material
- Lightguide material: PMMA
- TPA: (PC) option
- Long life-time: 50,000 hours
- 5-year guarantee
- Supplied with Tridonic fixed output driver
- 2.34 kg without driver
- 4000K or 3000K CRI80

Options

- TPA: PC
- DALI, 3 hour emergency
- For concealed grid metal ceiling system versions supplied with (CGB) bracket
- Surface mounting: Frame (SMF)
- Suspended mounting: suspended via adjustable wire suspension (3000mm)
- 4 fixing points to the ceiling. (S4P)



Add suffix to catalogue number:

- DALI:** Digital Addressable Lighting Interface.
- PD :** Phase dimming.SD: Dimming with push to make switch.
- EM3:** 3 hour emergency. **EM3ST:** 3 hour self test emergency.
- EM3DALI:** DALI addressable emergency.

Please note that with the continuous rapid development in lighting technology, specification values may change. Contact our technical department for details. We reserve the right to amend or change details without prior notification. All performance data is taken at an ambient temperature of +25°C. Lumens and connected system load are subject to an initial tolerance of up to +/- 10%.

**LEDFLATMODULARLUMINAIRESLIM
SPECIFICATION**

| CAT No | Watts | Lumens | CRI | Colour Temp (K) |
|---------|-------|--------|-----|-----------------|
| LRP2084 | 20 | 2100 | 80 | 4000 |
| LRP2684 | 27 | 2850 | 80 | 4000 |
| LRP3084 | 30 | 3150 | 80 | 4000 |
| LRP3684 | 36 | 3800 | 80 | 4000 |

