

- Semi-recessed mounted LED luminaire drop down side optics allow a percentage of light to be thrown up onto the ceiling and walls giving an aesthetically styled solution
- It eliminates dark ceilings which occur with downlight only schemes
- Powder coated white enclosed steel body
- Provision for gripper wire
- Central Microprismatic optic for Glare>19, optionally opal optic for perfect uniform illumination
- Opal diffuser
- An ideal modular for the high-tech interior schemes
- Fits most ceiling types, exposed T-bar 15 or 25mm
- Concealed grid, spring tee, SAS, metal pan, and mdf using side support arms
- ECA and L2 compliant
- IP40

**Options**

- DALI dimmable
- 3 hour emergency version
- Self test, DALI addressable emergency
- Conforms to EN60598-2-1 BS4533 C €




**Add suffix to catalogue number:**

**CG:** Concealed grid. **ST:** Spring tee metal pan.  
**E3:** Integral 3 hour emergency. **ST3:** Self Test emergency.  
**DE3:** DALI emergency. **DD:** DALI. **MP:** Micro prismatic. **OP:** Opal optic.


Please note that with the continuous rapid development in lighting technology, specification values may change. Contact our technical department for details. We reserve the right to amend or change details without prior notification. All performance data is taken at an ambient temperature of +25°C. Lumens and connected system load are subject to an initial tolerance of up to +/- 10%.

**SIDEWINDER SPECIFICATION**

CAT No	Colour Temp (K)	Colour Rendering (RA)	Life (L80) (hrs)	Total Delivered Lumens (lm)	Connected Load Total Watts (tcw)	Luminaire System Efficacy (lm/W)
SWX2184	4000	80	60000	2570	21	122
SWX2484	4000	80	60000	2827	24	118
SWX3084	4000	80	60000	3470	30	116
SWX3484	4000	80	60000	3810	34	112
SWX3884	4000	80	60000	4050	38	107
SWX2183	3000	80	60000	2390	21	114
SWX2483	3000	80	60000	2690	24	112
SWX3083	3000	80	60000	3300	30	110
SWX3483	3000	80	60000	3570	34	105
SWX3883	3000	80	60000	3870	38	102



Micro prismatic central optic



Opal central optic