



- Surface mounted LED Gimbal
- Available in matt white or black powder coated body
- Option, polished chrome, brushed chrome or any RAL colour.
- Providing an excellent luminaire efficacy up to 136lm/W
- Stable colour temperature options: 2700, 3000, 3500, 4000 kelvin
- CRI80/CRI90
- 60000 hour



**Add suffix to catalogue number:**

- SD:** Switch DIM dimming with push to make switch.
- DALI:** Digital Addressable Lighting Interface. **W:** White bezel.
- PC:** Polished chrome bezel. **SP:** Specify RAL Colour.

Please note that with the continuous rapid development in lighting technology, specification values may change. Contact our technical department for details. We reserve the right to amend or change details without prior notification. All performance data is taken at an ambient temperature of +25°C. Lumens and connected system load are subject to an initial tolerance of up to +/- 10%.

**Single Head**

CAT No	Total Delivered Lumens LOR 100%	Connected Load Total Watts (tcw)	Luminaire System Efficacy (lm/W)	W / H / L mm
GF9	1290	9.5	136	180x140x180
SGF113	1750	13.5	130	180x140x180
SGF119	2490	19	131	180x140x180
SGF23	2880	23	125	180x140x180
SGF127	3400	27	126	180x140x180

**Twin Head**

CAT No	Total Delivered Lumens LOR 100%	Connected Load Total Watts (tcw)	Luminaire System Efficacy (lm/W)	W / H / L mm
SGF29	2580	19	136	180x140x340
SGF213	3500	27	130	180x140x340
SGF219	4980	38	131	180x140x340
SGF223	5760	46	125	180x140x340
SGF227	6800	54	126	180x140x340

**Triple Head**

CAT No	Total Delivered Lumens LOR 100%	Connected Load Total Watts (tcw)	Luminaire System Efficacy (lm/W)	W / H / L mm
SGF39	3870	28.5	136	180x140x495
SGF313	5250	40.5	130	180x140x495
SGF319	7470	57	131	180x140x495
SGF323	8640	69	125	180x140x495
SGF327	10200	81	126	180x140x495