



- High performance LED track luminaire
- Die cast aluminium
- Passive thermal cooling with 26 or 44 degree beam
- Zero iridescence aluminium reflector
- Up to 3500lumen output, finished in black, white and silver or any RAL Finish to order
- Available with single or three circuit global track adaptor
- Can be surface mounted without track, surface plate GA70 providing an excellent luminaire efficacy up to 120 lumens lm/W
- Stable colour temperatures 2700K, 3000K, 3500K, 4000K CR180 90
- Available with DSI 1-10v and DALI dimmable LED driver
- ECA and L2 COMPLIANT
- Conforms to EN60598 BS4533

**Add suffix to catalogue number:**

**SD:** Dimming with push to make switch. **DALI:** Digital Addressable Lighting Interface. **W:** White RAL 9010. **BK:** Black RAL 9005.

**S:** Silver RAL 9006. **SP:** Any RAL colour. **26R:** 26° Reflector.

**44R:** 44° Reflector.

Please note that with the continuous rapid development in lighting technology, specification values may change. Contact our technical department for details. We reserve the right to amend or change details without prior notification. All performance data is taken at an ambient temperature of +25°C. Lumens and connected system load are subject to an initial tolerance of up to +/- 10%.

**CR180**

CAT No	Colour Temp (K)	Colour Rendering (RA)	Life (L80) (hrs)	Total Delivered Lumens (lm)	Connected Load Total Watts (tcw)	Luminaire System Efficacy (lm/W)
T1 984	4000	CRI 80	60000	1290	9.5	135.79
T1 9835	3500	CRI 80	60000	1250	9.5	131.58
T1 983	3000	CRI 80	60000	1200	9.5	126.32
T1 982	2700	CRI 80	60000	1170	9.5	123.16
T1 1384	4000	CRI 80	60000	1750	13.5	129.63
T1 13835	3500	CRI 80	60000	1710	13.5	126.67
T1 1383	3000	CRI 80	60000	1690	13.5	125.19
T1 1382	2700	CRI 80	60000	1640	13.5	121.48
T1 1984	4000	CRI 80	60000	2490	19	131.05
T1 19835	3500	CRI 80	60000	2443	19	128.58
T1 1983	3000	CRI 80	60000	2300	19	121.05
T1 1982	2700	CRI 80	60000	2270	19	119.47
T1 2484	4000	CRI 80	60000	2880	23	125.22
T1 24835	3500	CRI 80	60000	2850	23	123.91
T1 2483	3000	CRI 80	60000	2800	23	121.74
T1 2482	2700	CRI 80	60000	2700	23	117.39
T1 2784	4000	CRI 80	60000	3400	27	125.93
T1 27835	3500	CRI 80	60000	3330	27	123.33
T1 2783	3000	CRI 80	60000	3200	27	118.52
T1 2782	2700	CRI 80	60000	3100	27	114.81

**CR190**

T1 984	4000	CRI 90	60000	1093	9.5	115.05
T1 9835	3500	CRI 90	60000	1050	9.5	110.53
T1 983	3000	CRI 90	60000	1023	9.5	107.68
T1 982	2700	CRI 90	60000	1531	9.5	161.16
T1 1394	4000	CRI 90	60000	1498	13.5	110.96
T1 13935	3500	CRI 90	60000	1478	13.5	109.48
T1 1393	3000	CRI 90	60000	1435	13.5	106.30
T1 1392	2700	CRI 90	60000	1400	13.5	103.70
T1 1994	4000	CRI 90	60000	2137	19	112.47
T1 19935	3500	CRI 90	60000	2012	19	105.89
T1 1993	3000	CRI 90	60000	1986	19	104.53
T1 1992	2700	CRI 90	60000	2520	19	132.63
T1 2494	4000	CRI 90	60000	2495	23	108.48
T1 24935	3500	CRI 90	60000	2450	23	106.52
T1 2493	3000	CRI 90	60000	2370	23	103.04
T1 2492	2700	CRI 90	60000	2975	23	129.35
T1 2794	4000	CRI 90	60000	2920	27	108.15
T1 27935	3500	CRI 90	60000	2800	27	103.70
T1 2793	3000	CRI 90	60000	2720	27	100.74
T1 2792	2700	CRI 90	60000	2712	27	100.44