



- Twister LED recessed linear suitable for 1200 x 300 ceiling systems
- Sloping ribbed side panels give the luminaire an aesthetically styled solution
- High light output, balanced with good quality lit environment
- It eliminates dark ceilings which occur with downlight only schemes whether units are installed in rows or individually or in-line
- Powder coated white enclosed steel body,
- Multiple lens options for the centre
- Side panels allow you to achieve the appropriate light upon the ceiling and illumination for each space
- Provision for gripper wire
- An ideal modular for the high-tech interior schemes
- Fits most ceiling types, exposed t-bar 15 or 25mm
- Concealed grid, spring tee, SAS, metal pan and mdf using side support arms
- Fits perfectly in a variety of business and institutional settings including offices, schools and hospitals
- The centre panel available as matt Opal LED optic or Microprism
- Microprism optic illumination To EN 12464-1 UGR<19 LG7:2015
- Opal optic for enhanced light transmission and perfect uniform illumination

TWISTERLED LINEAR SPECIFICATION

CAT No	Colour Temp (K)	Colour Rendering (RA)	Life (L80) (hrs)	Total Connected Load	Total Delivered Lumens	Circuit Efficacy (lm/W)
TWLX48	4000	80	60000	5690	48	118.54
TWLX64	4000	80	60000	7320	64	114.37



Options

- DALI dimmable
- 3 hour emergency version
- Self test, DALI Addressable emergency
- Conforms to BS EN60598 C €

Add suffix to catalogue number:

CG: Concealed grid. **ST:** Spring tee metal pan.
E3: Integral 3 hour emergency.
ST3: Self test emergency. **DE3:** DALI emergency.
DD: DAL.

Please note that with the continuous rapid development in lighting technology, specification values may change. Contact our technical department for details. We reserve the right to amend or change details without prior notification. All performance data is taken at an ambient temperature of +25°C. Lumens and connected system load are subject to an initial tolerance of up to +/- 10%.