



- Semi-recessed wave luminaire giving an aesthetically styled solution
- High light output, balanced with good quality lit environment
- It eliminates dark ceilings which occur with downlight only schemes
- Powder coated white enclosed steel body
- IP40 standard, IP44 available
- Provision for gripple wire
- An ideal modular for the high-tech interior schemes
- Fits most ceiling types, exposed T-bar 15 or 25mm.
- Concealed grid, spring tee, SAS, metal pan and mdf using side support arms
- ECA and L2 Compliant

**Options**

- DALI dimmable
- 3 hour emergency version
- Self test, DALI addressable emergency
- Conforms to BS EN60598 C €

**WAVE SPECIFICATION**

CAT No	Colour Temp (K)	Colour Rendering (RA)	Life (L80) (hrs)	Total Delivered Lumens (lm)	Connected Load Total Watts (tcw)	Luminaire System Efficacy (lm/W)
WAX2983	3000	80	60000	3100	29	106.90
WAX2984	4000	80	60000	3200	29	110.34
WAX3683	3000	80	60000	5650	36	156.94
WAX3684	4000	80	60000	3790	36	105.28
WAX4283	3000	80	60000	4190	42	99.76
WAX4284	4000	80	60000	4320	42	102.86
WAX6483	3000	80	60000	5750	64	89.84
WAX6484	4000	80	60000	5920	64	92.50



**Add suffix to catalogue number:**

**CG:** Concealed grid. **ST:** Spring tee metal pan.  
**E3:** Integral 3 hour emergency. **ST3:** Self test emergency  
**DE3:** DALI emergency. **DD:** DALI.

Please note that with the continuous rapid development in lighting technology, specification values may change. Contact our technical department for details. We reserve the right to amend or change details without prior notification. All performance data is taken at an ambient temperature of +25°C. Lumens and connected system load are subject to an initial tolerance of up to +/- 10%.

