


- Recessed LED downlight UGR>19 IP54
- Tridonic COB led 60000h L80
- Aluminium body
- Supplied with Tridonic LED driver wide degree
- Bezel available in white RAL9003, RAL701 anthracite, RAL9006 grey, RAL9005 black

- CRI80 4000K
- CRI90 3000K
- CRI90 2700K



**Options**

- DALI,3 hour emergency
- Push to dim, 1-10v dimming
- Trailing, leading edge dimming
- Phase cut dim
- 5 year warranty
- Conforms to BS4533 EN60598 **CE**



**Add suffix to catalogue number:**

**DD:** Dali DSI. **E3:** 3 hour emergency. **ST3:** Self test emergency.  
**DE3:** Dali emergency. **BK:** Black, **W:** White bezel. **A:** Anthracite. **G:** Grey  
 4K, 3K or 27K Kelvin

Please note that with the continuous rapid development in lighting technology, specification values may change. Contact our technical department for details. We reserve the right to amend or change details without prior notification. All performance data is taken at an ambient temperature of +25°C. Lumens and connected system load are subject to an initial tolerance of up to +/- 10%.

**X44IP54LEDDOWNLIGHT  
SPECIFICATION**

REF	Watts	Lumens	Bezel mm	Height mm	Cut out mm
X4428	28	2990	230	62	185-220
X4425	25	2670	230	62	185-220
X4420	20	2140	190	55	160-180
X4415	15	1590	165	55	130-150
X4412	12	1290	145	50	125-135
X4410	10	1090	110	50	80-100

