



**X8**

Cut out: 60mm  
Bezel: 70mm  
Height: 85mm



**XS8**

Cut out: 60mm x 60mm  
Bezel: 70mm  
Height: 85mm



**XG8 Gimbal**

Cut out: 70mm  
Bezel: 80mm  
Height: 85mm

- 9w recessed LED downlight
- Die cast aluminium passive thermal cooling management housing
- Faceted highly-reflective zero iridescence aluminium reflector
- Direct replacement for 50W
- White bezel as standard, available with brushed chrome, black or any RAL colour
- Supplied with remote driver
- CRI90, 2700K, 3000K warm white or 4000K daylight
- Dimming options, DALI, DSI Switch DIM, 1-10v, trailing and leading edge
- 3 hour emergency versions
- 38° beam reflector
- Supplied with fixed output driver
- Weight .4kg
- Mains voltage 220-240V
- Mains frequency 50 / 60 Hz
- Operating ambient temperature: -25°C to +30°C
- Can be connected to 220 DC central battery
- Conforms to EN60 598-2-2 BS4533 C €

**X8 SPECIFICATION**

CAT No	Colour Temp (K)	Colour Rendering (RA)	Life (L70) (hrs)	Total luminous Output (lm)	Connected Load Total Watts (tcw)	Luminaire System Efficacy (lm/W)
X830	3000	90	50000	750	9	83.33
X840	4000	90	50000	830	9	92.22
XS830	3000	90	50000	750	9	83.33
XS840	3000	90	50000	830	9	92.22
XG830	3000	90	50000	750	9	83.33
XG840	4000	90	50000	830	9	92.22



**Add suffix to catalogue number:**

**EM:** 3 hour emergency. **EMST:** 3 hour self test emergency.

**EM3DALI:** DALI Addressable emergency. **W:** White bezel.

**BS:** Brushed chrome. **SP:** Any Ral colour please specify.

Please note that with the continuous rapid development in lighting technology, specification values may change. Contact our technical department for details. We reserve the right to amend or change details without prior notification. All performance data is taken at an ambient temperature of +25°C. Lumens and connected system load are subject to an initial tolerance of up to +/- 10%.